

1. A retransmission control method comprising the steps of:

each of said base stations performing
error judgment for said signal sent from said mobile
station;

said corresponding base station sending a response which indicates that retransmission is not required to said mobile station when said results includes a result indicating no error; and

25

base stations receiving a signal sent from
a mobile station;

said base stations exchanging results of
said error judgment with one another;

35 - a corresponding base station sending a
response which indicates that retransmission is not
required to said mobile station when results of said

5 said corresponding base station returning
a response which indicates that retransmission is
required to said mobile station when every result of
said error judgment of said base stations indicates
that there is an error.

3. The retransmission control method as claimed in claim 2, wherein a received signal power level of said signal in said corresponding base station is the largest among received signal power levels in said base stations.

4. A retransmission control apparatus in a base station, comprising:

25 a part performing error judgment for said
signal sent from said mobile station;

30 a part sending a response which indicates
that retransmission is not required to said mobile
station when said results includes a result
indicating no error; and

a part sending a response which indicates that retransmission is required to said mobile station when every result in said results indicates that there is an error.

5. A retransmission control apparatus in a
5 base station, comprising:

a part receiving a signal sent from a
mobile station;

a part performing error judgment for said
signal sent from said mobile station;

10 a part exchanging results of said error
judgment with other base stations;

a part returning a first response which
indicates that retransmission is not required to
said mobile station when results of said error
15 judgment of said base station and said other base
stations include a result indicating no error; and

a part returning a second response which
indicates that retransmission is required to said
mobile station when every result of said error
20 judgment of said base station and said other base
stations indicates that there is an error.

25

6. The retransmission control apparatus as
claimed in claim 5, wherein said first response or
said second response is sent to said mobile station
when a received signal power level of said signal in
30 said base station is larger than any received signal
power level in said other base stations.

35

44-1922300